

Optional ice handling accessories

SmartCART 75 ice cart

Perfect for moving small quantities of ice to manually fill storage receptacles. Transports 75 lb (34 kg) of ice at one time. Includes 3 Totes ice carriers for easy pouring. Stainless cart with easy-clean removable poly liner and fold-back lid.



SmartCART 125 ice cart

Fully insulated poly with flip-up lid makes an excellent working cart for portable bars. Transports 125 lb (57 kg) of ice at one time.



Cambro® cart -ICS125L

Fully insulated poly and slide back lid is perfect for sliding under bars. Transports 125 lb (57 kg) of ice at one time.



SmartCART 240 ice cart

Fully insulated poly with removable lid. Perfect for transporting large quantities of ice. Transports up to 240 lb (109 kg) of ice at one time. Shown with Totes ice carriers accessory (holds 150 lb (68 kg) of ice when Totes ice carriers are used).



Totes ice carrier

Comfortable handle, easy distribution of ice from longer side. Poly construction for strength and durability. Limits lifted load to 25 lb (11 kg).



Bagger kit

Makes manually bagging ice easy. Bagger kit includes bagger assembly, tape dispenser with tape and 250 plastic bags of 10 lb (4.5 kg) capacity.



801 Church Lane
Easton, PA 18040
follettice.com

Phone: 1.610.252.7301
1.800.523.9361
Fax: 1.610.250.0169

Distributed by:

Double door Ice•Devce ice storage and dispensing systems

- ice storage from 2110 to 4640 lb (957 to 2105 kg)
- gravity loading of ice through chute into Totes ice carrier when chute door is opened
- eliminates shoveling and scooping
- first ice in is first ice out
- standard with two door assemblies, two chutes and two 75 lb (34 kg) SmartCART ice carts
- can be configured with a manual bagger kit



DEV2250-72-75

Model Number	Max. bin capacity lb (kg)	Width in (cm)	Depth* in (cm)	Height in (cm)	Required door access in (cm)
DEV2100SG-72	2110 (957)	72.00 (182.9)	40.00 (101.6)	75.50 (191.8)	41.00 (104.1)
DEV2250SG-72	2250 (1021)	72.00 (182.9)	48.00 (121.9)	69.50 (176.5)	46.00 (116.8)
DEV2650SG-72	2650 (1202)	72.00 (182.9)	40.00 (101.6)	85.50 (217.2)	41.00 (104.1)
DEV3200SG-72	3240 (1470)	72.00 (182.9)	48.00 (121.9)	88.50 (224.8)	35.00 (88.9)
DEV3900SG-72	3940 (1787)	72.00 (182.9)	48.00 (121.9)	100.50 (255.3)	44.00 (111.8)
DEV4600SG-72	4640 (2105)	72.00 (182.9)	48.00 (121.9)	112.00 (284.5)	47.00 (119.4)

* Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access).

Ice transport systems (ITS)

- ice storage from 382 to 3255 lb (174 to 1477 kg), excluding carts; each cart stores an additional 240 lb (109 kg) of ice
- optional Totes ice carriers for SmartCART 240 ice cart limits lifted load to 25 lb (11 kg) for safe, easy ice distribution in displays, salad bars, ice dispensers
- each bay comes standard with one SmartCART 240 ice cart – configurable with 1, 2 or 3 SmartCART ice cart bays
- gravity loading of ice through access door at the bottom of the bin – easy ice retrieval
- eliminates the need to shovel or scoop ice from a bin
- 15 times faster than shoveling



ITS1350SG-60

Model Number	No. of Doors	Max. bin capacity lb (kg)	Width in (cm)	Depth* in (cm)	Height in (cm)	Required door access in (cm)
ITS500NS-31**	1	382 (174)	31.00 (78.7)	40.00 (101.6)	60.00 (152.4)	32.00 (81.3)
ITS700SG-31	1	652 (296)	31.00 (78.7)	40.00 (101.6)	75.00 (190.5)	32.00 (81.3)
ITS1350SG-60	2	1327 (602)	60.00 (152.4)	40.00 (101.6)	75.00 (190.5)	41.00 (104.1)
ITS2250SG-60	2	2133 (968)	60.00 (152.4)	40.00 (101.6)	97.00 (246.4)	41.00 (104.1)
ITS1700SG-90	3	1716 (779)	228.6 (90.00)	40.00 (101.6)	70.00 (177.8)	41.00 (104.1)
ITS3250SG-90	3	3255 (1477)	228.6 (90.00)	40.00 (101.6)	97.00 (246.4)	41.00 (104.1)

* Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access). Model ITS500NS-31 not equipped with door.

** ITS500NS-31 has sliding windows only, no SmartGATE ice shield or poly door.

Ice Pro automatic ice bagging and dispensing systems

- ice storage from 650 to 1000 lb (295 to 454 kg)
- 8 lb (3.6 kg) bags of packaged ice can be filled by one person at a rate of 6 per minute
- eliminates the need to shovel or scoop ice from a bin

Model Number	Max. bin capacity lb (kg)	Width in (cm)	Depth in (cm)	Height in (cm)	Required door access in (cm)
DB650SA	650 (295)	33.75 (85.7)	48.25 (122.6)	66.50 (168.9)	34.25 (87.0)
DB1000	1000 (454)	52.00 (132.1)	46.75 (118.7)	71.75 (182.2)	34.25 (87.0)
DB1000SA	1000 (454)	52.00 (132.1)	46.75 (118.7)	71.75 (182.2)	34.25 (87.0)



DB650SA



Ice Storage Ice Transport | Ice Handling



Follett ice storage, ice transport and ice handling equipment

Complete line of products for all your ice storage, transport and handling needs

- For use with commercial ice machines
- Can be configured for most applications

Powerful design features make ice transport easier, quicker, safer

SmartGATE® ice shield

- slides up smoothly for controlled access to ice – safely controls ice flow for minimal ice spillage
- dislodge minor ice bridges by sliding SmartGATE up and down
- permits bridge breaking through access slots – reduces risk of injury when bridge dislodges

FIFO – First ice in; first ice out

- first ice made is first ice used, delivering fresher, cleaner tasting ice
- FIFO product line: Upright bins, Ice•Devlce™ chuted bin and cart systems, ice storage and transport systems (ITS) and Ice Pro™ automatic ice bagging and dispensing bins vs slope front bins which first ice in is last ice out

PowerHinge™ door hinge

- one hand open and close – no awkward catches
- three position lock
- no clumsy latches, no unexpected closures

3-day lead time for shipment from order receipt

Slope front ice storage bins

- ice storage up to 1030 lb (467 kg)
- standard with stainless top, front and sides
- standard non-corroding polyethylene-lined walls
- ice is accessed through top-mounted door

Model Number	Max. bin capacity lb (kg)	Width in (cm)	Depth in (cm)	Height in (cm)	Required door access in (cm)
300-22	300 (136)	22.00 (55.9)	29.50 (74.9)	40.00 (101.6)	23.00 (58.4)
425-30	430 (195)	30.00 (76.2)	29.50 (74.9)	40.00 (101.6)	31.00 (78.7)
650-44	660 (299)	44.00 (111.8)	29.50 (74.9)	40.00 (101.6)	32.00 (81.2)
950-48	950 (431)	48.00 (121.9)	28.25 (71.8)	50.00 (127.0)	32.00 (81.2)
1025-52	1030 (467)	52.00 (132.1)	28.25 (71.8)	50.00 (127.0)	32.00 (81.2)



950-48

Single door upright ice storage bins with SmartGATE ice shield

- ice storage from 460 to 1660 lb (209 to 753 kg)
- easy to clean, corrosion-resistant ABS/poly tops
- complete stainless exterior
- easy removal of ice with scoop or shovel through access door at the bottom of the bin
- first ice made is first ice used

Model Number	No. of Doors	Max. bin capacity lb (kg)	Width in (cm)	Depth* in (cm)	Height in (cm)	Required door access in (cm)
SG500S-30	1	460 (209)	30.00 (76.2)	31.00 (78.7)	44.50 (113.0)	31.00 (78.7)
SG700S-30	1	680 (308)	30.00 (76.2)	31.00 (78.7)	60.00 (152.4)	31.00 (78.7)
SG1000-36**	1	990 (449)	36.00 (91.4)	31.00 (78.7)	69.50 (176.5)	32.00 (81.3)
SG860S-48	1	860 (390)	48.00 (121.9)	31.00 (78.7)	46.50 (118.1)	32.00 (81.3)
SG1010S-48	1	1000 (454)	48.00 (121.9)	31.00 (78.7)	56.00 (142.4)	32.00 (81.3)
SG1175S-48	1	1185 (538)	48.00 (121.9)	31.00 (78.7)	62.00 (157.5)	32.00 (81.3)
SG1300S-48	1	1320 (599)	48.00 (121.9)	31.00 (78.7)	65.00 (165.1)	32.00 (81.3)
SG1160S-56	1	1170 (531)	56.00 (142.2)	31.00 (78.7)	56.00 (142.2)	32.00 (81.3)
SG1350S-56	1	1360 (617)	56.00 (142.2)	31.00 (78.7)	62.00 (157.5)	32.00 (81.3)
SG1080S-60	1	1080 (490)	60.00 (152.4)	31.00 (78.7)	46.50 (118.1)	32.00 (81.3)
SG1325S-60	1	1325 (601)	60.00 (152.4)	31.00 (78.7)	56.00 (142.2)	32.00 (81.3)
SG1475S-60	1	1490 (676)	60.00 (152.4)	31.00 (78.7)	62.00 (157.5)	32.00 (81.3)
SG1650S-60	1	1660 (753)	60.00 (152.4)	31.00 (78.7)	65.00 (165.1)	32.00 (81.3)



SG1010S-48

* Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access).
** Available only with stainless steel top. Correctional package not available.

Double door upright ice storage bins with SmartGATE ice shield

- ice storage from 1870 to 4640 lb (848 to 2105 kg)
- easy to clean, corrosion-resistant ABS/poly tops
- complete stainless exterior
- easy removal of ice with scoop or shovel through access door at the bottom of the bin
- first ice made is first ice used



SG2250-72

Model Number	No. of Doors	Max. bin capacity lb (kg)	Width in (cm)	Depth* in (cm)	Height in (cm)	Required door access in (cm)
SG1850-96	2	1870 (848)	96.00 (243.8)	31.00 (78.7)	51.00 (129.5)	32.00 (81.3)
SG2100-72	2	2110 (957)	72.00 (182.9)	40.00 (101.6)	57.00 (144.8)	41.00 (104.1)
SG2250-72	2	2250 (1021)	72.00 (182.9)	48.00 (121.9)	50.50 (128.3)	46.00 (116.8)
SG2650-72	2	2650 (1202)	72.00 (182.9)	40.00 (101.6)	66.50 (168.9)	41.00 (104.1)
SG3200-72	2	3240 (1470)	72.00 (182.9)	48.00 (121.9)	69.50 (176.5)	35.00 (88.9)
SG3900-72	2	3940 (1787)	72.00 (182.9)	48.00 (121.9)	81.50 (207.0)	44.00 (111.8)
SG4600-72	2	4640 (2105)	72.00 (182.9)	48.00 (121.9)	93.00 (236.2)	47.00 (119.4)

* Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access).

Single door Ice•Devlce ice storage and dispensing systems

- ice storage from 460 to 1660 lb (209 to 753 kg)
- gravity loading of ice through chute into Totes™ ice carrier when chute door is opened
- eliminates shoveling and scooping
- 7 times faster than scooping
- first ice made is first ice used
- may be purchased with 75 lb (34 kg), 125 lb (57 kg) or 240 lb (109 kg) SmartCART™ ice cart
- can be configured with a manual bagger kit



DEV1010SG-48-75

Model Number	Max. bin capacity lb (kg)	Width in (cm)	Depth* in (cm)	Height** in (cm)	Required door access in (cm)
DEV500SG-30	460 (209)	30.00 (76.2)	31.00 (78.7)	63.00 (160.0)	31.00 (78.7)
DEV700SG-30	680 (308)	30.00 (76.2)	31.00 (78.7)	78.50 (199.4)	31.00 (78.7)
DEV860SG-48	860 (390)	48.00 (121.9)	31.00 (78.7)	65.50 (166.4)	32.00 (81.3)
DEV1010SG-48	1000 (454)	48.00 (121.9)	31.00 (78.7)	74.50 (189.2)	32.00 (81.3)
DEV1175SG-48	1185 (538)	48.00 (121.9)	31.00 (78.7)	80.50 (204.5)	32.00 (81.3)
DEV1300SG-48	1320 (599)	48.00 (121.9)	31.00 (78.7)	84.00 (213.4)	32.00 (81.3)
DEV1160SG-56	1170 (531)	56.00 (142.2)	31.00 (78.7)	74.50 (189.2)	32.00 (81.3)
DEV1350SG-56	1360 (617)	56.00 (142.2)	31.00 (78.7)	80.50 (204.5)	32.00 (81.3)
DEV1080SG-60	1080 (490)	60.00 (152.4)	31.00 (78.7)	65.50 (166.4)	32.00 (81.3)
DEV1325SG-60	1325 (601)	60.00 (152.4)	31.00 (78.7)	74.50 (189.2)	32.00 (81.3)
DEV1475SG-60	1490 (676)	60.00 (152.4)	31.00 (78.7)	80.50 (204.5)	32.00 (81.3)
DEV1650SG-60	1660 (753)	60.00 (152.4)	31.00 (78.7)	84.00 (213.4)	32.00 (81.3)

* Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access).
** Deduct 14.75" (375 mm) for low profile "LP" model configurations.